

Link do produktu: <https://www.wamm.pl/aida-hd-ndi-cube-po-demo-p-3008.html>

AIDA HD-NDI-CUBE - PO DEMO



Cena brutto	1 471 zł
Cena netto	1 196 zł
Cena poprzednia	2 235 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	HD-NDI-CUBE
Producent	AIDA Imaging

Opis produktu

AIDA HD-NDI-CUBE **NDI®|HX Compatible FHD POV Camera**

Don't let the HD-NDI-CUBE fool you. Its tiny form factor does not compromise any FULL-HD quality seen in our POV cameras. With the ability to output NDI|HX, SRT, RTSP and RTMP simultaneously, its no wonder why the CUBE is a production game-changer.

MAIN FEATURES

- Full-HD 1/3" Progressive Scan CMOS sensor capable of 1080 60p NDI®|HX Video.
- Accessible Web UI to stream directly to social media platforms and control image parameters over IP.
- Versatile design with top and bottom tripod mounts for unique shot creation.
- USB SVC port for easy network setting adjustments and updates.
- Small form-factor makes it placeable in discreet places
- Perfectly suited as extra angles for any new or existing NDI®|HX setup.

VIDEO

- Image Sensor 1/3" Progressive CMOS
- Sensor Size 5.346mm x 3.003mm (16.9)
- Effective Pixels Horizontal: 1920, Vertical: 1080
- Pixel Size 2.75 µm (H) x 2.75 µm (V)
- Resolution 1080p, 1080i, 720p
- Resolution Rate 1080 60p/59.94/50p/30p/29.97p/25p/24p
1080 60i/59.94i/50i
720 60p/59.94p/50p
- Output IP (NDI|HX/SRT/RTMP/RTSP)
- Color Space 4:2:2 (YCbCr) 10bit
- Min Illumination 0.2Lux (day), 0.1Lux (Night)
- White Balance Auto & Manual (9000 - 11,000 K)

LENS

- Lens C/CS Mount (Default 4mm HD Lens)

STANDARD

- IP Protocol UDP|IP, RTSP|RTMP, SRT, NDI|HX

PHYSICAL

- Camera Control Protocol: VISCA Over IP
- Operation Temp 32°F - 104°F

- Dimension 86mm x 40mm x 40mm /
3.38" x 1.57" x 1.57" (with default 4mm lens)
- Weight 180g / 0.39lbs (with default 4mm lens)
- Power 12VDC (+9 - +15VDC) (PoE Adapter Included)