

Link do produktu: <https://www.wamm.pl/aida-ptz-x12-ip-broadcastconference-fhd-ipsdihdmiusb3-ptz-camera-12x-zoom-p-2698.html>



AIDA PTZ-X12-IP | Broadcast/Conference FHD IP/SDI/HDMI/USB3 PTZ Camera 12X Zoom

Cena brutto	5 658 zł
Cena netto	4 600 zł
Dostępność	Zapytaj o dostępność
Numer katalogowy	PTZ-X12-IP
Kod producenta	PTZ-X12-IP
Producent	AIDA Imaging

Opis produktu

AIDA PTZ-X12-IP | Broadcast/Conference FHD IP/SDI/HDMI/USB3 PTZ Camera 12X Zoom

The PTZ-X12-IP is one of AIDA's most well-rounded Full HD cameras yet. The camera features IP streaming technology by H.264 or the newer H.265 High Efficiency Video Coding (HEVC). With integrated RS232 and VISCA over IP camera control, this camera is compatible with most IP based controllers, simplifying existing workflows with better cable management. The camera features traditional multi video format outputs such as 3G-SDI, HDMI, USB 3.0, as well as online video outputs RTSP/RTMP. Our camera's cost effective approach makes professional grade PTZ cameras, at the fraction of the price.

Video

Image Sensor	1/2.5" Progressive CMOS
Effective Pixels	Horizontal: 1920, Vertical: 1080
Pixel Size	2.13 μm x 2.13 μm
Resolution	1080p & 1080i: 1920 x 1080
Resolution/Rate	1080 60p/59.94p/50p/30p/29.97p/25p/24p/23.98p 1080 60i/59.94i/50i 720 60p/59.94p/50p/30p/29.97p/25p
IP Rate	1920 x 1080 @ 1~60 1280 x 720 @ 1~60 1024 x 576 @ 1~60 620 x 360 @ 1~60
Output	HD-SDI/3G-SDI HDMI RJ45 USB 3.0 & 2.0
Color Space	4:2:2 (YCbCr) 10bit
Min. Illumination	0.1Lux
Function	
White Balance	Auto, Manual, Auto Tracking, One Push, Indoor, Outdoor
Focus	Auto, Manual
Shutter Speed	1 to 1/10,000 Sec.
Lens	

Lens	12X HD Optical Zoom, F1.5 ~ F3.0
PTZ	
Pan/Tilt Range	Pan: 340°, Tilt: +90 to -30°
Pan/Tilt Speed	Pan: 0° to +120°/s, Tilt: 0° to +80°/s,
Presets	128 Positions
Field of View	72.5°
Standard	
SMPTE	SMPTE 292M, SMPTE 424M
IP Protocol	TCP/IP, RTSP/RTMP
Physical	
Camera Control	Protocol: VISCA Interface: RS-232C IN & OUT, RJ-45 Remote Controller
Operation Temp	32° F - 104° F
Dimension	155mm x 160mm x 170mm / 6.10" x 6.92" x 6.69"
Weight	1.35kg / 2.97lbs
Power	12VDC (+9 - +15VDC)