

Link do produktu: <https://www.wamm.pl/datavideo-ptc-150tl-hdsd-ptz-hdbaset-bez-odbiornika-hbt-11-i-zasilacza-p-2369.html>



DataVideo PTC-150TL HD/SD PTZ HDBaseT | bez odbiornika HBT-11 i zasilacza

Cena brutto	11 231 zł
Cena netto	9 131 zł
Dostępność	Zapytaj o dostępność
Producent	Datavideo

Opis produktu

DataVideo PTC-150T

HD/SD PTZ Video Camera with HDBaseT Technology

The PTC-150TL HD/SD Video Camera is a PTZ camera that can be mounted on a wall, ceiling, floor, or a tabletop. The camera is equipped with HDBaseT Technology for remote control purpose, video image conveyance, power transmission and Ethernet connection. The camera captures HD video at 1920 x 1080 resolution and features wide dynamic range with backlight compensation. The camera features a motorized 30x optical zoom capability and its image mirror and image rotation functions allow you to electronically adjust the image and deliver a correctly orientated image. In addition to the basic camera functions, the PTC-150TL also has a receiver box that allows the user to control the camera at a remote location with just one Ethernet cable.

50 programmable presets including pan, tilt, and zoom positions, allow the camera to quickly move between predetermined camera positions using the remote, or an available PTZ controller.

For multi camera shoots, the built in tally light can identify active camera. The camera features a built in IR cut filter in the image path for low light shooting and

then returns for daytime shooting. Also, PTC-150TL supports real time position report on a per frame basis; this is helpful in a virtual studio application.

The camera supports Sony VISCA protocol for PTZ control using RS-422 interface over the unit's RJ-45 port.

Features:

- HD/SD PTZ Video Camera with HDBaseT Technology
- HD Resolution: 1/2.8" High Definition 2.0 M Pixels progressive CMOS sensor
- 30x optical zoom (f = 4.3 mm to 94.6 mm)
- High definition formats supported: 1080/59.94p, 1080/50p, 1080/59.94i, 1080/29.97p, 1080/25p, 1080/50i, 720/59.94p, 720/50p
- Standard definition formats supported: 480i, 576i
- Digital Noise Reduction Function (DNR) to reduce the noise and enable clearer image under low light conditions.
- Position coordinates report in real time per frame.
- Video Output: HD-SDI + CVBS + HDMI synchronously.
- Tally LED Design (IR / RF Controller / RS-422 / DVIP Operation)
- Supports VISCA Protocol Keyboard
- Supports VIP Control Protocol

WARUNKI Gwarancji do 36 miesięcy

Warunkiem uzyskania gwarancji do **36 miesięcy** jest wymagana **obowiązkowa rejestracja** produktów w terminie **30 dni od dnia zakupu**. W przypadku braku rejestracji obowiązuje standardowa gwarancja **12 miesięcy od daty zakupu**.

[Link do rejestracji produktów](#) [Rejestracja](#)