Dane aktualne na dzień: 12-11-2026 12:54

Link do produktu: https://www.wamm.pl/kiloview-n6-hd-hdmindi-bi-directional-converter-p-3236.html



Kiloview N6 | HD HDMI/NDI Bi-Directional Converter

Cena brutto	**2 467 zł**
Cena netto	**2 006 zł**
Dostępność	**Zapytaj o dostępność**
Kod producenta	**N6**
Producent	**Kiloview**

Opis produktu

Kiloview N6
HD HDMI/NDI Bi-Directional Converter

Kiloview N6 HDMI/NDI converter is a bi-directional converter that supports HDMI input (encoder) to both NDI high bandwidth and NDI|HX2/3 with loop through for view on monitor, or HDMI video output (decoder) from any NDI sources coming from any camera, software or device from any brand, either from NDI high bandwidth or NDI|HX2/3.

Featured with powerful functions such as PoE, LCD display with big-sized tally , PTZ control, 3.5mm audio line in/out, multi-channel audio, intercom functions, centralized management, N6 is the easiest way to get access to the fabulous NDI world for low latency and high image quality with versatile choices.

2-IN-1 for NDI Encoding & Decoding
Kiloview N6 supports encoding/decoding of NDI High Bandwidth and NDI|HX2/3. Both NDI encoding and decoding can work within this compact device. Switch the working mode on the UI to the mode you want, and it can easily accommodate all of your workflows.

In encoding mode, N6 can encode HDMI signal into an NDI High Bandwidth/NDI|HX2/3 video stream.
In decoding mode, N6 will automatically adapt the NDI High Bandwidth/NDI|HX2/3 and output through HDMI.

Audio And Intercom
Kiloview N6 supports 3.5mm analog audio line in/out or embedded audio. Max 4 CH audio encoding will be supported.

It also supports voice intercom between all Kiloview devices and the control PC/phone, with Kiloview Intercom server.

Built-in LCD Screen and Touch Button
N6 is equipped with a 1.14-inch LCD screen with touch buttons for a better user experience. With the built-in LCD screen, you can easily check the connectivity, IP address, CPU, memory, resolution, temperature, and tally status in real-time.

Seamless Switching
In decoding mode, you can preset up to 9 NDI sources from the web UI and choose one to output without suffering from black screen, flashing and lagging.

PTZ Control
Kiloview N6 supports PTZ control through USB to serial RS232/485/422. It also supports PTZ control over IP with different protocols, no extra cable required.

Power It as You Wish
With PoE, the N6 can be powered with a single cable connection. With the design of wide DC input range from 5V to 18V, it can also be easily powered by USB power or a camera battery.