Dane aktualne na dzień: 12-11-2026 12:58

Link do produktu: https://www.wamm.pl/magewell-pro-capture-hdmi-4k-plus-jednokanalowa-karta-przechwytujaca-4k-p-2193.html



Magewell Pro Capture HDMI 4K Plus | Jednokanałowa karta przechwytująca 4K

Cena brutto	**4 622 zł**
Cena netto	**3 758 zł**
Dostępność	**Zapytaj o dostępność**
Kod producenta	**11150**
Producent	**Magewell**

Opis produktu

Magewell Pro Capture HDMI 4K Plus


Jednokanałowa karta przechwytująca 4K

Magewell Pro Capture HDMI 4K Plus to wysokowydajna karta przechwytująca PCIe o niskim opóźnieniu, z dodatkowymi funkcjami przepustowości. Ta jednokanałowa karta PCI 4K przechwytuje sygnały HDMI z osadzonym dźwiękiem i obsługuje rozdzielczość do 4096×2160 pikseli.

Modele Pro Capture automatycznie wykrywają format sygnału wejściowego, zapewniając niezawodne, wysokiej jakości przechwytywanie wideo i audio dla profesjonalistów wideo, integratorów systemów oraz deweloperów OEM. Ponadto cechują się przetwarzaniem wideo opartym na FPGA Magewell, które nie obciąża procesora, zapewniając wysokiej jakości konwersję w górę/w dół oraz regulacje obrazu bez zużywania cennej mocy obliczeniowej systemu hosta.

Urządzenia Pro Capture obsługują systemy operacyjne Windows, Linux i macOS – w tym architektury x86, x64 oraz ARM – i oferują szeroką kompatybilność z popularnym oprogramowaniem do streamingu, produkcji na żywo, konferencji internetowych, nagrywania wykładów, współpracy oraz obrazowania medycznego. Magewell MWCapture SDK zapewnia zarówno ogólne interfejsy, jak i niestandardowe API na wszystkich platformach systemowych, pomagając deweloperom w pełni wykorzystać możliwości sprzętu Magewell i osiągnąć niższe opóźnienia, wielostrumieniowe przechwytywanie oraz synchronizację AV w wielokanałowym lub nawet wielokartowym przechwytywaniu.

Magewell Pro Capture HDMI 4K to doskonałe rozwiązanie do przechwytywania wysokiej jakości sygnałów wideo i audio, idealne dla wymagających profesjonalistów.



Tech Specs

Supported OS	• Windows
	  ◦ Windows 7/8/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2016 (x86 & x64)
	• Linux (support x86, x64 & ARM architecture)
	  ◦ Ubuntu 12.04/14.04/16.04/17.04/17.10 (x86 & x64)
	  ◦ CentOS 6.5/7 (x86 & x64)
	  ◦ Fedora 25/26/27 (x86 & x64)
	  ◦ Red hat 6.5 and above (x86 & x64)
	  ◦ Other Linux OS with kernel version 2.6.35 and above
	• Mac
	  ◦ OS X 10.9/10.10/10.11
	  ◦ macOS 10.12/10.13

Recommended OS (tested)	• Windows
	  ◦ Windows 7 Ultimate/8.1 Enterprise/10 Enterprise/Server 2008 R2 DataCenter/Server 2012 R2 DataCenter/Server 2016 R2 DataCenter (x86 & x64)
	• Linux
	  ◦ Ubuntu 12.04/14.04/16.04 (x86 & x64)
	  ◦ Ubuntu 17.04/17.10 (x64)
	  ◦ CentOS 6.5/7.2 (x86 & x64)
	  ◦ Fedora 25/26 (x64)
	  ◦ Red hat 6.5 (x86 & x64)
	• Mac
	  ◦ OS X 10.9.5/10.10/10.11.2/10.11.3/10.11.4
	  ◦ macOS 10.12/10.13.2/10.13.3

Supported APIs	• Windows
	  ◦ DirectShow
	  ◦ DirectKS
	  ◦ Wave API/DirectSound/WASAPI

Supported Software	• VLC • VirtualDub • OBS • XSplit • vMix • VidBlaster • Wirecast • Microsoft Media Encoder • Adobe Flash Media Encoder • Any other DirectShow/V4L2 encoding/streaming software

Input Interfaces	• HDMI
	  ◦ DVI-D 1.0
	  ◦ HDMI 2.0

Host Interfaces	• PCIe Gen2 x4

wamm
video solutions

Input Features

- Support for input video resolutions up to 4096×2160 pixels

HDMI Specific Features

- 594MHz HDMI receiver
- Adaptive HDMI equalizer
- Support for customized EDID
- Support for extraction of AVI/Audio/SPD/MS/VS/ACP/ISRC1/ISRC2/Gamut InfoFrames
- Full colorimetry support
- Support for 8/10/12-bit color depths
- Support for RGB 4:4:4, YCbCr 4:4:4, YCbCr 4:2:2 color sampling
- Support for up to 8-channel IEC60958/IEC61937 audio streams
- Support for extraction of audio formation information & channel status data
- Support for extraction of video timing information
- Support for extraction of 3D format information
- Support for extraction of Sony/Canon DSLR time code
- Support for Side-by-Side Half, Top-and-Bottom, Frame Packing 3D mode

Video Capture Formats

- Support for capture image resolutions up to 4096×2160 pixels
- Support for capture frame rates up to 144fps. (Actual capture frame rate can be limited by PCIe bandwidth & image resolution)
- Support for 4:2:0 8-bit capture formats: NV12, I420, YV12
- Support for 4:2:2 8-bit capture formats: YUY2, YUYV, UYVY
- Support for 4:4:4 8-bit capture formats: V308, IYU2, V408, BGR24, BGR32
- Support for 4:4:4 10-bit capture formats: V410, Y410
- More capture formats are supported via Pro Capture SDK for DirectKS

Video Processing Features

- Two video processing pipelines with ~720Mpixels/s processing bandwidth
- Full 10-bit video processing
- Video cropping
- Video scaling
- Video de-interlacing
    - Weave
    - Blend top & bottom field
    - Top field only
    - Bottom field only
- Video aspect ratio conversion
    - Auto or manual selection of input aspect ratio
    - Auto or manual selection of capture aspect ratio
    - Three aspect ratio conversion modes: Ignore (Anamorphic), Cropping or Padding (Letterbox or Pillarbox)
- Video color format conversion
    - Auto or manual selection of input color format

	& quantization range ◦ Auto or manual selection of capture color format, quantization range & saturation range ◦ Support for RGB, YCbCr 601, YCbCr 709, YCbCr 2020 color formats ◦ Support for Limited or Full quantization range ◦ Support for Limited, Full & 'Extended gamut' saturation range • Video frame rate conversion • Video OSD composition ◦ Support for PNG OSD image (up to 4096×2160) ◦ Support for dynamic loading of RGBA OSD image via SDK
Multiple Cards per System	• Support for multiple cards plugged to one system • On-board rotary switch to set card number, with 16 positions from 0 to F • System hardware device tree will display "01: Pro Capture HDMI 4K+" when rotary switch is set to 1, and so on • The video and audio device names displayed in your software will include the card number (set by the rotary switch)
Multiple Capture Streams	• Unlimited capture streams for any one input channel • Independent cropping, aspect ratio, color format, resolution, frame rate, de-interlacing and color adjustment settings for each individual stream
Ultra Low Latency Support	• Latency of 64 video lines • Partial notification mode in SDK
Timestamp &A/V Synchronization	• Hardware based 100ns high resolution clock • Audio frames (192 audio samples) & video frames are stamped with hardware clock • Hardware clock can be synchronized across cards (via SDK)
Video Capture SG-DMA	• ~1600MB/s per channel DMA bandwidth in PCIe 2.x system • ~800MB/s per channel DMA bandwidth in PCIe 1.x system • Support for auto detection of Intel tiled GPU surface • Support for DirectGMA for AMD video adapter chipsets • Support for GPUDirect for Nvidia video adapter chipsets
SDK	• Pro Capture SDK for DirectShow for easy integration (Windows) • Pro Capture SDK for DirectKS for maximum flexibility & performance (Windows)

Windows Driver Tweaks	• All options can be controled by three levels of registry key: global level, product level and device level • Video,Audio, Crossbar filter names can be customized via registry keys
Firmware Upgrade	• Multiple cards in one system can be upgraded simultaneously • Cards can be upgraded without a system power shutdown (In most cases, even a reboot is not needed)
LED Indicator	• Status LEDs indicate the working state of each channel: idle, input signal locked, memory failed or FPGA configuration failed.
Form Factor	• Low profile PCIe x4 Add-on Card • 140mm x 68.88mm (without PCI bracket)
Power Consumption	• Max current at 12V: ~ 0.48 A • Max current at 3.3V: ~ 0.82 A • Max power consumption: ~ 8.08 W
Working Environment	• Operating temperature: 0 to 40 deg C • Storage temperature: –20 to 70 deg C • Relative Humidity: 5% to 90% non-condensing