

Link do produktu: <https://www.wamm.pl/marshall-electronics-cv620-ipw-ptz-broadcast-camera-ipethernet-3ghd-sdi-hdmi-output-white-p-2610.html>



Marshall Electronics CV620-IPW | PTZ Broadcast Camera IP/Ethernet, 3G/HD-SDI & HDMI Output (White)

Dostępność	Zapytaj o dostępność
Numer katalogowy	CV620-IPW
Kod producenta	CV620-IPW
Producent	Marshall Electronics

Opis produktu

Marshall Electronics CV620-IPW | PTZ Broadcast Camera IP/Ethernet, 3G/HD-SDI & HDMI Output (Black)

Built around a 1/2.8" 2-megapixel sensor, the **Marshall Electronics CV620-IPW HD PTZ Camera** is a versatile, professional camera designed for corporate, broadcast, houses of worship, medical, legal, or any other professional industry which requires HD video from a remote-controllable PTZ camera.

Not only does the CV620-IPW feature HDMI and broadcast-ready SDI outputs, the Ethernet connection allows for IP network integration. Not only is the Ethernet connection for video, but control and PoE (Power over Ethernet) are supported as well, allowing for single-cable connection. Video can be transmitted over the network in easy-to-implement MJPEG or H.264 variants. All outputs are active simultaneously.

While camera settings can be adjusted automatically, manual control over white balance, exposure, iris, gamma, gain, black level, and more are available for those that require fine image control.

Features:

- 1/2.8" sensor captures clear images
- 1080p, 1080i, and 720p modes
- 20x optical zoom (4.7 to 94mm) with 12x digital zoom extension
- Mountable via table, wall, ceiling mounts included with flippable images
- Simultaneous output over SDI, HDMI, and Ethernet
- RS422/RS232 Remote Control Interface
- Compatible with integrated video conferencing systems
- Quiet PTZ motors won't disturb recorded audio

Specyfikacje

Sensor	Size: 1/2.8" Resolution: 2 MP
Supported Resolutions	1080p 25/29.97/30/50/59.94/60 1080i 50/59.94/60 720p 50/59.94/60
Lens	Focal Length: 4.7-94mm Aperture: f/1.6-3.5 Zoom: 20x optical with 12x digital
Minimum Object Distance	Wide: 12" / 30 cm Tele: 60" / 1.5 m
Minimum Illumination	1 lux (50 IRE at f/1.6 and 30 fps)
Shutter Speed	1 - 1/10,000 sec
S/N Ratio	> 50 dB
Video Compression Format	MJPEG, H.264 (SVC)

Pan/Tilt Angle	Pan: $\pm 170^{\circ}$ Tilt: -30 to $+90^{\circ}$
I/O	1 x BNC, HD/3G-SDI output 1 x HDMI type A output 1 x RJ45, Ethernet 1 x 3.5mm, stereo analog audio 1 x DIN, RS-232 input 1 x DIN, RS-232 output 1 x 9-pin Phoenix, RS-422 1 x USB, firmware
Dimensions	6.85 x 7.32 x 7.19" / 17.4 x 18.6 x 18.5 cm
Weight	4.4 lb / 2 kg